

R4

Date of printing 28/1/2026

Technical data

NOTE: The photo shows a general example of the product.

| | |
|--------------------------------|-------------------|
| [MaximumMachineWeight] | 10000 - 16000 kg |
| [MaximumBucketWidth] | 1600 mm |
| [MaximumBreakingForce] | 125 kN |
| [MaximumBreakingTorque] | 163 kNm |
| [WeightFrom] | 380 kg |
| [TiltAngle] | 40° |
| [RotationSpeed] | 7.0 s at 60 l/min |
| [WorkingPressure] | 25 MPa |
| [MinHydraulicFlow] | 91 l/min |
| [NrOfLubricationPoints] | 6 |
| [TurnTorque] | 7640 Nm at 25 MPa |
| [TiltTorqueA] | 26500 Nm |
| [TiltTorqueB] | 38600 Nm |



Measurement specification

| Dimension A, Width | Dimension B, Installation height total | Dimension C, Length | Dimension D, Installation height |
|---------------------------|---|----------------------------|---|
| 729 mm | 1037 mm | 705 mm | 503 mm |

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

