

# R1

Date of printing 16/09/2025

## Technical data

NOTE: The photo shows a general example of the product.

<b>Machine weight, max</b>	1500 - 3500 kg
<b>Max bucket width</b>	1000 mm
<b>Max breakout force</b>	35 kN
<b>Max. breakout torque</b>	25 kNm
<b>Weight (from)</b>	90 kg
<b>Tilt angle (2x)</b>	40°
<b>Rotation speed (1 turn in)</b>	7.0 s at 15 l/min
<b>Working pressure</b>	21 MPa
<b>Recomended hydraulic flow min</b>	21 l/min
<b>Nr of lubrication points</b>	5
<b>Turn torque</b>	1650 Nm at 21 MPa
<b>Tilt torque double acting cylinders</b>	5800 Nm



## Measurement specification

<b>Dimension A, Width</b>	<b>Dimension B, Installation height total</b>	<b>Dimension C, Length</b>	<b>Dimension D, Installation height</b>
290 mm	1150 mm	456 mm	333 mm

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

