

# RC1

Date of printing 28/04/2026

## Technical data

NOTE: The photo shows a general example of the product.

<b>Machine weight, max</b>	1500 - 3500 kg
<b>Max bucket width</b>	1000 mm
<b>Max breakout force</b>	35 kN
<b>Max. breakout torque</b>	25 kNm
<b>Weight (from)</b>	115 kg
<b>Tilt angle (2x)</b>	40°
<b>Rotation speed (1 turn in)</b>	7.0 s at 15 l/min
<b>Working pressure</b>	21 MPa
<b>Recomended hydraulic flow max</b>	21 l/min
<b>Nr of lubrication points</b>	5
<b>Turn torque</b>	1650 Nm at



## Measurement specification

<b>Dimension A, Width</b>	<b>Dimension B, Installation height total</b>	<b>Dimension C, Length</b>	<b>Dimension D, Installation height</b>
416 mm	701 mm	481 mm	335 mm

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

