

# RC2

Date of printing 29/06/2026

## Technical data

NOTE: The photo shows a general example of the product.

|                                      |                   |
|--------------------------------------|-------------------|
| <b>Machine weight, max</b>           | 3000 - 6500 kg    |
| <b>Max bucket width</b>              | 1200 mm           |
| <b>Max breakout force</b>            | 50 kN             |
| <b>Max. breakout torque</b>          | 43 kNm            |
| <b>Weight (from)</b>                 | 170 kg            |
| <b>Tilt angle (2x)</b>               | 40°               |
| <b>Rotation speed (1 turn in)</b>    | 7.0 s at 30 l/min |
| <b>Working pressure</b>              | 25 MPa            |
| <b>Recomended hydraulic flow max</b> | 42 l/min          |
| <b>Turn torque</b>                   | 3900 Nm at        |



## Measurement specification

| <b>Dimension A, Width</b> | <b>Dimension B, Installation height total</b> | <b>Dimension C, Length</b> | <b>Dimension D, Installation height</b> |
|---------------------------|---|----------------------------|---|
| 314 mm                    | 810 mm  | 468 mm                     | 389 mm                                  |

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.