

# RC4

Date of printing 31/07/2025

## Technical data

NOTE: The photo shows a general example of the product.

<b>Machine weight, max</b>	10000 - 16000 kg
<b>Max bucket width</b>	1600 mm
<b>Max breakout force</b>	125 kN
<b>Max. breakout torque</b>	163 kNm
<b>Weight (from)</b>	395 kg
<b>Tilt angle (2x)</b>	40°
<b>Rotation speed (1 turn in)</b>	7.0 s at 60 l/min
<b>Working pressure</b>	25 MPa
<b>Recomended hydraulic flow min</b>	91 l/min
<b>Recomended hydraulic flow max</b>	91 l/min
<b>Nr of lubrication points</b>	6
<b>Turn torque</b>	7600 Nm at 25 MPa
<b>Tilt torque double acting cylinders</b>	38600 Nm



## Measurement specification

<b>Dimension A, Width</b>	<b>Dimension B, Installation height total</b>	<b>Dimension C, Length</b>	<b>Dimension D, Installation height</b>
760 mm	1080 mm	690 mm	568 mm

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

