

# RC9

Date of printing 05/02/2026

## Technical data

NOTE: The photo shows a general example of the product.

<b>Machine weight, max</b>	32000 - 43000 kg
<b>Max standard bucket volume</b>	2.3 m <sup>3</sup>
<b>Max bucket width</b>	2400 mm
<b>Max breakout force</b>	280 kN
<b>Max. breakout torque</b>	500 kNm
<b>Weight (from)</b>	1480 kg
<b>Tilt angle (2x)</b>	40°
<b>Rotation speed (1 turn in)</b>	8.0 s at 126 l/min
<b>Working pressure</b>	35 MPa
<b>Recomended hydraulic flow min</b>	206 l/min
<b>Recomended hydraulic flow max</b>	206 l/min
<b>Nr of lubrication points</b>	2
<b>Turn torque</b>	19100 Nm at 25 MPa
<b>Tilt torque double acting cylinders</b>	90000 Nm



## Measurement specification

Dimension A, Width	Dimension B, Installation height total	Dimension C, Length	Dimension D, Installation height
1363 mm	1582 mm	1164 mm	773 mm

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

