R3

Date of printing 5/9/2025

Technical data

NOTE: The photo shows a general example of the product.

Machine weight, max13230 - 26455 lbMax bucket width59 inMax breakout force18210 lbfMax breakout torque62695 ft.lbWeight (from)661 lbTilt angle (2x)40°Rotation speed (1 rotation per)7.0 s at 13 gpmWorking pressure3626 psiMin hydraulic flow18.23 gpmNumber of lubrication points6Turning torque4499 ft.lb at 3626 psiTilt torque singe-acting cylinders15860 ft.lb	THE PHOLO SHOWS a general example	· · · · · · · · · · · · · · · · · · ·	
Max breakout force18210 lbfMax breakout torque62695 ft.lbWeight (from)661 lbTilt angle (2x)40°Rotation speed (1 rotation per)7.0 s at 13 gpmWorking pressure3626 psiMin hydraulic flow18.23 gpmNumber of lubrication points6Turning torque4499 ft.lb at 3626 psiTilt torque singe-acting cylinders15860 ft.lb	Machine weight, max	13230 - 26455 lb	
Max breakout torque62695 ft.lbWeight (from)661 lbTilt angle (2x)40°Rotation speed (1 rotation per)7.0 s at 13 gpmWorking pressure3626 psiMin hydraulic flow18.23 gpmNumber of lubrication points6Turning torque4499 ft.lb at 3626 psiTilt torque singe-acting cylinders15860 ft.lb	Max bucket width	59 in	
Weight (from) 661 lb Tilt angle (2x) 40° Rotation speed (1 rotation per) 7.0 s at 13 gpm Working pressure 3626 psi Min hydraulic flow 18.23 gpm Number of lubrication points 6 Turning torque 4499 ft.lb at 3626 psi Tilt torque singe-acting cylinders 15860 ft.lb	Max breakout force	18210 lbf	
Tilt angle (2x) 40° Rotation speed (1 rotation per) 7.0 s at 13 gpm Working pressure 3626 psi Min hydraulic flow 18.23 gpm Number of lubrication points 6 Turning torque 4499 ft.lb at 3626 psi Tilt torque singe-acting cylinders 15860 ft.lb	Max breakout torque	62695 ft.lb	
Rotation speed (1 rotation per) Working pressure Min hydraulic flow Number of lubrication points Turning torque Tilt torque singe-acting cylinders 7.0 s at 13 gpm 7.0 s at 13 gpm 18.23 gpm 44.99 ft.lb at 3626 psi 15860 ft.lb	Weight (from)	661 lb	
Working pressure 3626 psi Min hydraulic flow 18.23 gpm Number of lubrication points 6 Turning torque 4499 ft.lb at 3626 psi Tilt torque singe-acting cylinders 15860 ft.lb	Tilt angle (2x)	40°	
Min hydraulic flow18.23 gpmNumber of lubrication points6Turning torque4499 ft.lb at 3626 psiTilt torque singe-acting cylinders15860 ft.lb	Rotation speed (1 rotation per)	7.0 s at 13 gpm	
Number of lubrication points 6 Turning torque 4499 ft.lb at 3626 psi Tilt torque singe-acting cylinders 15860 ft.lb	Working pressure	3626 psi	
Turning torque 4499 ft.lb at 3626 psi Tilt torque singe-acting cylinders 15860 ft.lb	Min hydraulic flow	18.23 gpm	
Tilt torque singe-acting cylinders 15860 ft.lb	Number of lubrication points	6	
	Turning torque	4499 ft.lb at 3626 psi	
Till to your double noting ordinators 405.45 th	Tilt torque singe-acting cylinders	15860 ft.lb	
Thit torque double acting cylinders 19545 It.ID	Tilt torque double acting cylinders	19545 ft.lb	



Dimensions

	Dimension B, Installation height total		Dimension D, Installation height
26,65 in	36,97 in	23,9 in	18,39 in

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.



