

R3

Date of printing 12/13/2025

Technical data

NOTE: The photo shows a general example of the product.

| | |
|-------------------------------------|------------------------|
| Machine weight, max | 13230 - 26455 lb |
| Max bucket width | 59 in |
| Max breakout force | 18210 lbf |
| Max breakout torque | 62695 ft.lb |
| Weight (from) | 661 lb |
| Tilt angle (2x) | 40° |
| Rotation speed (1 rotation per) | 7.0 s at 13 gpm |
| Working pressure | 3626 psi |
| Min hydraulic flow | 18.23 gpm |
| Number of lubrication points | 6 |
| Turning torque | 4499 ft.lb at 3626 psi |
| Tilt torque singe-acting cylinders | 15860 ft.lb |
| Tilt torque double acting cylinders | 19545 ft.lb |



Dimensions

| Dimension A, Width | Dimension B, Installation height total | Dimension C, Length | Dimension D, Installation height |
|--------------------|--|---------------------|----------------------------------|
| 26,65 in | 36,97 in | 23,9 in | 18,39 in |

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

