Rototilt® Tiltrotators Page 1 of 1

RC9

Date of printing 7/30/2025

Technical data

NOTE: The photo shows a general example of the product.

Machine weight, max	70550 - 94800 lb		
Max standard bucket volume	81 cu ft		
Max bucket width	94 in		
Max breakout force	62945 lbf		
Max breakout torque	368780 ft.lb		
Weight (from)	3263 lb		
Tilt angle (2x)	40°		
Rotation speed (1 rotation per)	8.0 s at 33 gpm		
Working pressure	5076 psi		
Min hydraulic flow	54.42 gpm		
Recommended hydraulic flow	54 gpm		
Number of lubrication points	2		
Turning torque	14085 ft.lb at 3626 psi		
Tilt torque double acting cylinders	66380 ft.lb		



Dimensions

Dimension A, Width	Dimension B, Installation height total		Dimension D, Installation height
53,66 in	62,28 in	45,83 in	30,43 in

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.



