Rototilt® Tiltrotators Page 1 of 1

RC9

Date of printing 11/5/2025

Technical data

NOTE: The photo shows a general example of the product.

| · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | |
|---|---------------------------------------|--|
| Machine weight, max | 70550 - 94800 lb | |
| Max standard bucket volume | 81 cu ft | |
| Max bucket width | 94 in | |
| Max breakout force | 62945 lbf | |
| Max breakout torque | 368780 ft.lb | |
| Weight (from) | 3263 lb | |
| Tilt angle (2x) | 40° | |
| Rotation speed (1 rotation per) | 8.0 s at 33 gpm | |
| Working pressure | 5076 psi | |
| Min hydraulic flow | 54.42 gpm | |
| Recommended hydraulic flow | 54 gpm | |
| Number of lubrication points | 2 | |
| Turning torque | 14085 ft.lb at 3626 psi | |
| Filt torque double acting cylinders 66380 ft.lb | | |



Dimensions

| | Dimension B, Installation height total | | Dimension D, Installation height |
|----------|--|----------|--|
| 53,66 in | 62.28 in | 45,83 in | 30.43 in |

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.





