

# R3

Date of printing 1/28/2026

## Technical data

NOTE: The photo shows a general example of the product.

<b>Machine weight, max</b>	6000 - 12000 kg
<b>Max bucket width</b>	1500 mm
<b>Max breakout force</b>	81 kN
<b>Max. breakout torque</b>	85 kNm
<b>Weight (from)</b>	300 kg
<b>Tilt angle (2x)</b>	40°
<b>Rotation speed (1 turn in)</b>	7.0 s at 50 l/min
<b>Working pressure</b>	25 MPa
<b>Recomended hydraulic flow min</b>	69 l/min
<b>Nr of lubrication points</b>	6
<b>Turn torque</b>	6100 Nm at 25 MPa
<b>Tilt torque singe-acting cylinders</b>	21500 Nm
<b>Tilt torque double acting cylinders</b>	26500 Nm



## Measurement specification

Dimension A, Width	Dimension B, Installation height total	Dimension C, Length	Dimension D, Installation height
677 mm	939 mm	607 mm	467 mm

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

