## **R5**

Date of printing 11/5/2025

## Technical data

NOTE: The photo shows a general example of the product.

Machine weight, max 14000 - 19000 kg   Max bucket width 1700 mm		
Max bucket width 1700 mm		
	1700 mm	
Max breakout force 140 kN	140 kN	
Max. breakout torque 200 kNm	200 kNm	
Weight (from) 520 kg		
Tilt angle (2x) 40°		
Rotation speed (1 turn in) 7.0 s at 72 l/min	7.0 s at 72 l/min	
Working pressure 25 MPa	25 MPa	
Recomended hydraulic flow min 121 l/min	121 l/min	
Nr of lubrication points 6	6	
Turn torque 9550 Nm at 25 MPa	9550 Nm at 25 MPa	
Tilt torque singe-acting cylinders 30900 Nm		
Tilt torque double acting cylinders 45100 Nm	45100 Nm	



## Measurement specification

Dimension A, Width	Dimension B, Installation height total	Dimension C, Length	Dimension D, Installation height
800 mm	1150 mm	800 mm	530 mm

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.





