

# R5

Date of printing 2/13/2026

## Technical data

NOTE: The photo shows a general example of the product.

<b>Machine weight, max</b>	14000 - 19000 kg
<b>Max bucket width</b>	1700 mm
<b>Max breakout force</b>	140 kN
<b>Max. breakout torque</b>	200 kNm
<b>Weight (from)</b>	520 kg
<b>Tilt angle (2x)</b>	40°
<b>Rotation speed (1 turn in)</b>	7.0 s at 72 l/min
<b>Working pressure</b>	25 MPa
<b>Recomended hydraulic flow min</b>	121 l/min
<b>Nr of lubrication points</b>	6
<b>Turn torque</b>	9550 Nm at 25 MPa
<b>Tilt torque singe-acting cylinders</b>	30900 Nm
<b>Tilt torque double acting cylinders</b>	45100 Nm



## Measurement specification

<b>Dimension A, Width</b>	<b>Dimension B, Installation height total</b>	<b>Dimension C, Length</b>	<b>Dimension D, Installation height</b>
800 mm	1150 mm	800 mm	530 mm

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

