

# RC3

Date of printing 5/9/2026

## Technical data

NOTE: The photo shows a general example of the product.

<b>Machine weight, max</b>	6000 - 12000 kg
<b>Max bucket width</b>	1500 mm
<b>Max breakout force</b>	81 kN
<b>Max. breakout torque</b>	85 kNm
<b>Weight (from)</b>	310 kg
<b>Tilt angle (2x)</b>	40°
<b>Rotation speed (1 turn in)</b>	7.0 s at 50 l/min
<b>Working pressure</b>	25 MPa
<b>Recomended hydraulic flow max</b>	73 l/min
<b>Nr of lubrication points</b>	5
<b>Turn torque</b>	7600 Nm at



## Measurement specification

<b>Dimension A, Width</b>	<b>Dimension B, Installation height total</b>	<b>Dimension C, Length</b>	<b>Dimension D, Installation height</b>
646 mm	936 mm	679 mm	504 mm

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

