

RC5

Date of printing 12/13/2025

Technical data

NOTE: The photo shows a general example of the product.

| | |
|--|-------------------|
| <i>Machine weight, max</i> | 14000 - 19000 kg |
| <i>Max bucket width</i> | 1700 mm |
| <i>Max breakout force</i> | 140 kN |
| <i>Max. breakout torque</i> | 200 kNm |
| <i>Weight (from)</i> | 595 kg |
| <i>Tilt angle (2x)</i> | 40° |
| <i>Rotation speed (1 turn in)</i> | 7.0 s at 72 l/min |
| <i>Working pressure</i> | 25 MPa |
| <i>Recomended hydraulic flow min</i> | 121 l/min |
| <i>Turn torque</i> | 9550 Nm at 25 MPa |
| <i>Tilt torque double acting cylinders</i> | 56600 Nm |



Measurement specification

| <i>Dimension A, Width</i> | <i>Dimension B, Installation height total</i> | <i>Dimension C, Length</i> | <i>Dimension D, Installation height</i> |
|---------------------------|---|----------------------------|---|
| 819 mm | 1228 mm | 801 mm | 601 mm |

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

