

# RC8

Date of printing 3/8/2026

## Technical data

NOTE: The photo shows a general example of the product.

<b>Machine weight, max</b>	23000 - 32000 kg
<b>Max bucket width</b>	2000 mm
<b>Max breakout force</b>	200 kN
<b>Max. breakout torque</b>	330 kNm
<b>Weight (from)</b>	840 kg
<b>Tilt angle (2x)</b>	40°
<b>Rotation speed (1 turn in)</b>	8.0 s at 129 l/min
<b>Working pressure</b>	25 MPa
<b>Recomended hydraulic flow min</b>	134 l/min
<b>Recomended hydraulic flow max</b>	134 l/min
<b>Nr of lubrication points</b>	5
<b>Turn torque</b>	11900 Nm at 25 MPa
<b>Tilt torque double acting cylinders</b>	64700 Nm



## Measurement specification

<b>Dimension A, Width</b>	<b>Dimension B, Installation height total</b>	<b>Dimension C, Length</b>	<b>Dimension D, Installation height</b>
950 mm	1333 mm	920 mm	673 mm

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

