Rototilt® Tiltrotators Sida 1 av 1

RC9

Date of printing 10/29/2025

Technical data

NOTE: The photo shows a general example of the product.

00000 40000 les			
Machine weight, max	32000 - 43000 kg		
Max standard bucket volume	2.3 m ³		
Max bucket width	2400 mm		
Max breakout force	280 kN		
Max. breakout torque	500 kNm		
Weight (from)	1480 kg		
Tilt angle (2x)	40°		
Rotation speed (1 turn in)	8.0 s at 126 l/min		
Working pressure	35 MPa		
Recomended hydraulic flow min	206 l/min		
Recomended hydraulic flow max	206 l/min		
Nr of lubrication points	2		
Turn torque	19100 Nm at 25 MPa		
Tilt torque double acting cylinders	90000 Nm		



Measurement specification

Dimension A, Width	Dimension B, Installation height total		Dimension D, Installation height
1363 mm	1582 mm	1164 mm	773 mm

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.





