R1

Date of printing 2025/09/07

Technical data

NOTE: The photo shows a general example of the product.

[MaximumMachineWeight] 1500 - 3500 kg [MaximumBucketWidth] 1000 mm [MaximumBreakingForce] 35 kN [MaximumBreakingTourque] 25 kNm [WeightFrom] 90 kg [TiltAngle] 40°
[MaximumBreakingForce] 35 kN [MaximumBreakingTourque] 25 kNm [WeightFrom] 90 kg
[MaximumBreakingTourque] 25 kNm [WeightFrom] 90 kg
[WeightFrom] 90 kg
[TiltAngle] 40°
[RotationSpeed] 7.0 s at 15 l/min
[WorkingPreassure] 21 MPa
[MinHydraulicFlow] 21 l/min
[NrOfLubricationPoints] 5
[TurnTorque] 1650 Nm at 21 MPa
[TiltTorqueB] 5800 Nm



Measurement specification

А,	Dimension B, Installation height total		Dimension D, Installation height
290	1150 mm	456	333 mm
mm		mm	

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.





