

# R2

Date of printing 2026. 2. 12.

## Technical data

NOTE: The photo shows a general example of the product.

<b>[MaximumMachineWeight]</b>	3000 - 6500 kg
<b>[MaximumBucketWidth]</b>	1200 mm
<b>[MaximumBreakingForce]</b>	50 kN
<b>[MaximumBreakingTorque]</b>	43 kNm
<b>[WeightFrom]</b>	175 kg
<b>[TiltAngle]</b>	40°
<b>[RotationSpeed]</b>	7.0 s at 30 l/min
<b>[WorkingPressure]</b>	25 MPa
<b>[MinHydraulicFlow]</b>	42 l/min
<b>[NrOfLubricationPoints]</b>	3
<b>[TurnTorque]</b>	3900 Nm at 25 MPa
<b>[TiltTorqueB]</b>	14400 Nm



## Measurement specification

<b>A,</b>	<b>Dimension B, Installation height total</b>	<b>C,</b>	<b>Dimension D, Installation height</b>
314 mm	810 mm	468 mm	389 mm

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

