

R5

Date of printing 2025. 9. 7.

Technical data

NOTE: The photo shows a general example of the product.

| | |
|--------------------------|-------------------|
| [MaximumMachineWeight] | 14000 - 19000 kg |
| [MaximumBucketWidth] | 1700 mm |
| [MaximumBreakingForce] | 140 kN |
| [MaximumBreakingTourque] | 200 kNm |
| [WeightFrom] | 520 kg |
| [TiltAngle] | 40° |
| [RotationSpeed] | 7.0 s at 72 l/min |
| [WorkingPreassure] | 25 MPa |
| [MinHydraulicFlow] | 121 l/min |
| [NrOfLubricationPoints] | 6 |
| [TurnTorque] | 9550 Nm at 25 MPa |
| [TiltTorqueA] | 30900 Nm |
| [TiltTorqueB] | 45100 Nm |



Measurement specification

| A, | Dimension B, Installation height total | C, | Dimension D, Installation height |
|--------|--|--------|----------------------------------|
| 800 mm | 1150 mm | 800 mm | 530 mm |

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

